SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 28 04 A15

Horizontal Datum: **NAD 83/91**
Vertical Datum: **NAVD 88**

Established By: C of E

Control Point ID: **Book:** **645** **Page:** 12 **Pt#:** 01 **Date:** 08/19/1996

Edited by Geodetic Consultants 7/1996
Revised by Geodetic Consultants 5/05/1997

Section: 03 Township: 28 N Range: 04 E

LATTITUDE: (5 decimal places) **47 56 58.26229**
LONGITUDE: (5 decimal places) **122 16 56.34840**

ORTHOMETRIC HEIGHT: **236.5** Feet
72.10 Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	**349697.486**	**1285350.648**	**0.999946555**	**-01 04 43.7**
Meters	**106588.0070**	**391775.6610**		

HORIZONTAL DATA:
Horizontal position established by: C of E using Rapid Static GPs
and constrained to
City Points VIEW, PAINE E079 and S137.
____ resection survey, comments ____
x GPS survey, GPS adjustment software used: Starnet GPS
____ other, explain: ____
surveyor's estimated relative positional accuracy: .01 ft. @ ____ 95 % confidence
surveyor's estimated absolute positional accuracy: ____ ft. @ ____ % confidence

VERTICAL DATA:
Vertical position established by:C of E using Rapid Static GPS and
constrained to
City points VIEW, PAINE and E079.
____ differential leveling to: ____ order accuracy
x GPS survey, accuracy within ____ ft ____ meters
surveyor's estimated relative positional accuracy: . .01. ft @ ____ 95% confidence
surveyor's estimated absolute positional accuracy: ____ ft @ ____ % confidence

MONUMENT DESCRIPTION

A 3/8 inch brass disk and lead plug set in the top of a 3x3 inch concrete post that projects 0.07 feet above the ground surface. By common report it is purported to be the North ¼ of Section 3, Township 28 North, Range 4 East.

TO REACH

From the intersection of West Mukilteo Boulevard and Upland Avenue, go south on Upland Avenue to house number 3608 Upland Avenue to the mark on the south side of the house.

REFERENCES

Az from North Distance Reference Description

8 feet south and 3.7 feet East of the southeast corner of the garage
4.05 feet south of the south face of the retaining wall
27.7 feet east of the west end of the retaining wall

Month & Year Recovered: Condition of Mark: Recovered By: