SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 28 05 F05

Horizontal Datum: **NAD83/91**
Vertical Datum: **NAVD88**
Established By: **DOT-Linn & Asso**
Control Point ID: **Book:** **703** **Page:** 68 **Pt#:** 02 **Date:** **9/09/1999**

Section: 08 Township: 28 N Range: 5 E

LATTITUDE: (5 decimal places) **47 55 58.00382**
LONGITUDE: (5 decimal places) **122 12 25.36914**

ORTHOMETRIC HEIGHT: _____ Feet
_____ Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	**343254.432**	**1303684.467**	**0.999947452**	**-01 01 21.9**
Meters	**104624.160**	**397363.875**		

HORIZONTAL DATA:
Horizontal position established by:
_____ resection survey, comments _____
x GPS survey, GPS adjustment software used: Trimble RTK, Trimbal Software
_____ other, explain: _____
surveyor's estimated relative positional accuracy: 0.4 ft n @ 0.4 ft E ___ 95% confidence Level Constrained to DOT points GP31005-81, through GP31005-88
surveyor's estimated absolute positional accuracy: ft @ 1 sigma _____ @___ % confidence Level
VERTICAL DATA:
Vertical position established by: WJA
_____ differential leveling to: _____ order accuracy
_____ GPS survey, accuracy within ___ ft _____ meters
surveyor's estimated relative positional accuracy: _____ ft @ ___ 95% confidence Level
surveyor's estimated absolute positional accuracy: ___ ft @ ____ 95% confidence

MONUMENT DESCRIPTION

A 2-inch diameter brass plug and tack in the top of a concrete monument down 3-inches under an iron monument case and cover

TO REACH

Located in the center of Wetmore Avenue about 150 feet south of the monument at the intersection of 72nd Place and Wetmore Avenue. It is purported to be the W 1/16 corner of the NW ¼ of Section 8 Township 28 North, Range 5 East.

REFERENCES

Az from North Distance Reference Description

Month & Year Recovered: Condition of Mark: Recovered By: