SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 28 05 R05

Horizontal Datum:
Vertical Datum:
Control Point ID: **Book:** **Page:** **Pt#:**

Established By: SNOCO
Date: 02/17/1998
Data sheet edited by Geodetic Consultants 03/31/1998

Section: 30 Township: 28N Range: 5E

LATTITUDE: (5 decimal places) **47 53 33.84565**
LONGITUDE: (5 decimal places) **122 12 24.60275**

ORTHOMETRIC HEIGHT: _____ Feet
_____ Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	**328648.895**	**1303476.138**	**0.999949942**	**-01 01 21.4**
Meters	**1000172.3835**	**397300.3215**		

HORIZONTAL DATA: SNOCO

_____ resection survey, comments _____
_____ GPS survey, GPS adjustment software used: _____
x other, explain: Position was established by Cadastral Calculations by the Snohomish County Survey Office.
surveyor's estimated relative positional accuracy: ___ .0 ft. @ ___ 95 % confidence
surveyor's estimated absolute positional accuracy: ___ ft. @ ___ % confidence

VERTICAL DATA:
Vertical position established by: Points
_____ differential leveling to: _____ order accuracy
_____ GPS survey, accuracy within _____ ft .05 Meters
surveyor's estimated relative positional accuracy: _____ ft @ _____ % confidence
surveyor's estimated absolute positional accuracy: _____ ft @ _____ % confidence

MONUMENT DESCRIPTION

The Corner falls in Silver Lake. The [position was established by a single proportion by the Snohomish County Survey Office. The Meander Corner Positions were existing monumentation and record information.

TO REACH

REFERENCES

Az from North Distance Reference Description

Month & Year Recovered: Condition of Mark: Recovered By: