SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 614 11 02

Horizontal Datum:
Vertical Datum:
Control Point ID: **Book:** **614** **Page:** 11 **Pt#:** 02

Established By: H&AI
Date: 10/15/1995
Data sheet edited by Geodetic Consultants 1995
Readjusted by H&AI in 1997

Section: 13 Township: 28N Range: 4E

LATTITUDE: (5 decimal places) **47 54 57.13531**
LONGITUDE: (5 decimal places) **122 14 01.38042**

ORTHOMETRIC HEIGHT: **549** Feet
167.3 Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	**337205.728**	**1297035.692**	**0.99994844**	**-01 02 33.4**
Meters	**102780.5279**	**395337.2696**		

HORIZONTAL DATA: By H&AI using GPS Methods in 1991

___ resection survey, comments ___
X GPS survey, GPS adjustment software used: ___
___ other, explain: ___
surveyor's estimated relative positional accuracy: ___ .02ft. @ ___ 95 % confidence
surveyor's estimated absolute positional accuracy: ___ ft. @ ___ % confidence

VERTICAL DATA:

___ differential leveling to: 3
X GPS survey, accuracy within ___ ft .04. Meters
surveyor's estimated relative positional accuracy: ___ .0ft @ ___ % confidence
surveyor's estimated absolute positional accuracy: ___ ft @ ___ % confidence

MONUMENT DESCRIPTION

A concrete monument with a brass pin in lead, set under an iron monument case and cover.

TO REACH

.It is located just south of the intersection of Holly Drive and Evergreen Way.

REFERENCES

Az from North	Distance	Reference Description
	169.17 feet	Southeast of a railroad spike at the Southwest corner of arrow
	160.72 feet	North northeast of a railroad spike at the end of the parking area
	74.74 feet	Northwest of a 20-penny nail
	71.03 feet	Southwest of a 20-penny nail

onth & Year Recovered: Condition of Mark: Recovered By: