SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 639 02 G

Horizontal Datum: **NAD 83/91**
Vertical Datum: **NAVD 88**
Control Point ID: **Book:** **639** **Page:** 02 **Pt#:** G

Established By: Perteet Eng.
Date: 3/21/96
Revised by Geodetic Consultants 08/2000.

Section: 16 Township: 29 N Range: 05 E

LATTITUDE: (5 decimal places) **47** **59** **22.69484**
LONGITUDE: (5 decimal places) **122** **10** **09.41301**

ORTHOMETRIC HEIGHT: **15.84** Feet
4.828 Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	**363828.918**	**1313301.041**	**0.999944750**	**-00 59 40.7**
Meters	**110895.2761**	**400294.9578**		

HORIZONTAL DATA:
Horizontal position established by:
_____ resection survey, comments _____
X GPS survey, GPS adjustment software used: lEICA
_____ other, explain: _____
surveyor's estimated relative positional accuracy: .03 ft. @ ____ 95% confidence
surveyor's estimated absolute positional accuracy: ___ .04 ft. @ ____ 95% confidence

VERTICAL DATA:
Vertical position established by:
X differential leveling to: 3 order accuracy
_____ GPS survey, accuracy within _____ ft _____ meters
surveyor's estimated relative positional accuracy: ___ .06 ft @ _____ 95% confidence
surveyor's estimated absolute positional accuracy: _____ ft @ _____ % confidence

MONUMENT DESCRIPTION

5/8-inch rebar with aluminum cap stamped **CITY OF EVERETT SURVEY CONTROLL STATION 639-2G** set flush with the asphalt.

TO REACH

Located in the asphalt at the end of the road in the middle of the south sewer pond.

REFERENCES

Az from North Distance Reference Description

Month & Year Recovered: Condition of Mark: Recovered By: