SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 694 77 06

Horizontal Datum: **NAD83/91**
Vertical Datum: **NAVD88**

Established By: **Perteet Engineering Inc.**

Control Point ID: **Book:** **694** **Page:** 77 **Pt#:** 06 **Date:** **11/18/99**
Edited by Geodetic Consultants, 03/22/2000.

Section: 19 Township: 29N Range: 5 E

LATTITUDE: (5 decimal places) **47 58 43.45231**
LONGITUDE: (5 decimal places) **122 12 25.69577**

ORTHOMETRIC HEIGHT: _____ Feet
_____ Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	**360016.432**	**1303961.663**	**0.999945192**	**-01 01 22.2**
Meters	**109733.2281**	**397448.3103**		

HORIZONTAL DATA:
Horizontal position established by: Perteet Engineering Inc.
_____ resection survey, comments _____
_____ GPS survey, GPS adjustment software used: _____
_x_ other, explain: Closed traverse
surveyor's estimated relative positional accuracy: 0.1 ft n @ 0.1 ft E _____ ___ 95% confidence Level
surveyor's estimated absolute positional accuracy: 0.5 ft @ 1 sigma _____ @___ % confidence
VERTICAL DATA:
Vertical position established by:
_____ differential leveling to: _____ order accuracy
_____ GPS survey, accuracy within ___ ft _____ meters
surveyor's estimated relative positional accuracy: ___ ft @ ___ 95% confidence Level
surveyor's estimated absolute positional accuracy: ___ ft @ ____ 95% confidence
Correction to NGVD29: -1.122m. .

MONUMENT DESCRIPTION

A concrete monument with a brass pin in lead, set under an iron monument case and cover. That is 22 feet East and 194 feet South of the center of the intersection.

TO REACH

Located south of the intersection of Wetmore Avenue and Hewitt Avenue.

REFERENCES

Az from North Distance Reference Description

Month & Year Recovered: Condition of Mark: Recovered By: