# SURVEY RECOVERY FORM

**City of Everett**
**Department of Public Works**

**State of Washington**
**County: Snohomish**

## Station Name: 703 53 03

**Horizontal Datum:** **NAD83/91**
**Vertical Datum:** **NAVD88**
**Established By:** **DOT-Linn & Asso**
**Control Point ID:** **Book:** **703** **Page:** 53 **Pt#:** 03 **Date:** **9/8/99**

Section: 08 Township: 28 N Range: 5 E

**LATTITUDE:** (5 decimal places) **47 55 32.82953**
**LONGITUDE:** (5 decimal places) **122 11 55.43613**

**ORTHOMETRIC HEIGHT:** _____ Feet
_____ Meters

**Washington State Plane Coordinates – North Zone**

| | Northing (4 decimal places) | Easting (4 decimal places) | Point Scale Factor (to 9 decimal places) | Convergence Deg Min Sec |
|---|---|---|---|---|
| **Feet** | **340667.754** | **1305677.326** | **0.999947852** | **-01 00 59.6** |
| **Meters** | **103835.739** | **397971.245** | | |

**HORIZONTAL DATA:**
Horizontal position established by:
_____ resection survey, comments _____
_x_ GPS survey, GPS adjustment software used: Trimble RTK, Trimbal Software
_____ other, explain: _____
surveyor's estimated relative positional accuracy: 0.4 ft n @ 0.4 ft E ___ 95% confidence Level Constrained to DOT points GP31005-81, through GP31005-88
surveyor's estimated absolute positional accuracy: ft @ 1 sigma _____ @___ % confidence Level
**VERTICAL DATA:**
Vertical position established by: WJA
_____ differential leveling to: _____ order accuracy
_____ GPS survey, accuracy within ___ ft _____ meters
surveyor's estimated relative positional accuracy: _____ ft @ ___ 95% confidence Level
surveyor's estimated absolute positional accuracy: ___ ft @ ____ 95% confidence

## MONUMENT DESCRIPTION

A 4-inch concrete monument with a 2-inch lead plug and brass tack set in the top, down 3-inches under an iron monument case and cover.

## TO REACH

Located at the intersection of Larlin Drive and Timber Hill Circle.

## REFERENCES

Az from North Distance Reference Description

Month & Year Recovered: Condition of Mark: Recovered By: