SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 703 58 02

Horizontal Datum: **NAD83/91**
Vertical Datum: **NAVD88**
Established By: **DOT-Linn & Asso**
Control Point ID: **Book:** **703** **Page:** 58 **Pt#:** 02 **Date:** **9/10/99**

Section: 08 Township: 28 N Range: 5 E

LATTITUDE: (5 decimal places) **47 55 57.80578**
LONGITUDE: (5 decimal places) **122 11 38.57751**

ORTHOMETRIC HEIGHT: _____ Feet
_____ Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	**343177.765**	**1306870.017**	**0.999947455**	**-01 00 47.1**
Meters	**104600.792**	**398334.778**		

HORIZONTAL DATA:
Horizontal position established by:
_____ resection survey, comments _____
_x_ GPS survey, GPS adjustment software used: Trimble RTK, Trimbal Software
_____ other, explain: _____
surveyor's estimated relative positional accuracy: 0.4 ft n @ 0.4 ft E ___ 95% confidence Level Constrained to DOT points GP31005-81, through GP31005-88
surveyor's estimated absolute positional accuracy: ft @ 1 sigma _____ @___ % confidence Level
VERTICAL DATA:
Vertical position established by: WJA
_____ differential leveling to: _____ order accuracy
_____ GPS survey, accuracy within ___ ft _____ meters
surveyor's estimated relative positional accuracy: _____ ft @ ___ 95% confidence Level
surveyor's estimated absolute positional accuracy: ___ ft @ ____ 95% confidence

MONUMENT DESCRIPTION

A 1-3/4 inch brass plug with a punch mark set in the top of a concrete monument, down 7-inches under an iron monument case and cover.

TO REACH

Located at the center of Yew Street, at the end of a curve about 250 feet south of intersection of Juniper Drive and Yew Street.

REFERENCES

Az from North Distance Reference Description

Month & Year Recovered: Condition of Mark: Recovered By: