SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 726 15 01

Horizontal Datum: **NAD 83/91**
Vertical Datum: **NAVD 88**
Control Point ID: 726 **Book:** **Page:** 15 **Pt#:** 01

Established By: Perteet Eng.
Date: 03/06/2002
Edited by Geodetic Consultants 10/02/2002

Section: 20 Township: 29 N Range: 05 E

LATTITUDE: (5 decimal places) 47 59 04.37874
LONGITUDE: (5 decimal places) 122 12 09.98984

ORTHOMETRIC HEIGHT: 86.009 Feet
26.2157 Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	362117.457	1305067.753	0.999944952	-01 01 10.5
Meters	110373.7617	397785.4466		

HORIZONTAL DATA:
Horizontal position established by:
____ resection survey, comments ____
X GPS survey, GPS adjustment software used: Leica SVI-Prov2.1
____ other, explain: ____
surveyor's estimated relative positional accuracy: .01 ft. @ ____ 95 % confidence
surveyor's estimated absolute positional accuracy: ____ ft. @ ____ % confidence

VERTICAL DATA:
Vertical position established by:
X differential leveling to: 3 order accuracy Using a Leica NA2002 Digital level and fiberglass Barcode rods. BM used was V038.
____ GPS survey, accuracy within ____ ft ____ meters
surveyor's estimated relative positional accuracy: ____ .02 ft @ ____ 95% confidence
surveyor's estimated absolute positional accuracy: ____ ft @ ____ % confidence

MONUMENT DESCRIPTION

A concrete monument with a brass rod in a lead plug, set under an iron monument case and cover.

TO REACH

Located at the northeast corner of the intersection of Lombard Avenue and 25th Street.

REFERENCES

Az from North	Distance	Reference Description
NE	20.0 feet	Stop Sign

Month & Year Recovered: Condition of Mark: Recovered By: