SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 726 19 01

Horizontal Datum: **NAD 83/91**
Vertical Datum: **NAVD 88**

Established By: Perteet Eng.

Control Point ID: 726 **Book:** **Page:** 19 **Pt#:** 01

Date: 03/06/2002
Edited by Geodetic Consultants 10/02/2002

Section: 20 Township: 29 N Range: 05 E

LATTITUDE: (5 decimal places) 47 59 03.88000
LONGITUDE: (5 decimal places) 122 11 26.78013

ORTHOMETRIC HEIGHT: 77.888 Feet
23.7403 Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	362014.854	1308005.776	0.999944957	-01 00 38.3
Meters	110342.3483	398880.9580		

HORIZONTAL DATA:
Horizontal position established by:
____ resection survey, comments ____
X GPS survey, GPS adjustment software used: Leica SVI-Prov2.1
____ other, explain: ____
surveyor's estimated relative positional accuracy: .01 ft. @ ____ 95 % confidence
surveyor's estimated absolute positional accuracy: ____ ft. @ ____ % confidence

VERTICAL DATA:
Vertical position established by:
X differential leveling to: 3 order accuracy Using a Leica NA2002 Digital level and fiberglass Barcode rods. BM used was V038.
____ GPS survey, accuracy within ____ ft ____ meters
surveyor's estimated relative positional accuracy: ____ .02 ft @ ____ 95% confidence
surveyor's estimated absolute positional accuracy: ____ ft @ ____ % confidence

MONUMENT DESCRIPTION

A concrete monument with a punch mark in a lead plug, set under an iron monument case with no cover.

TO REACH

Located near the curb at the northeast corner of the intersection of Maple Street and 25th Street.

REFERENCES

Az from North	Distance	Reference Description
E	10.3 feet	Stop Sign

Month & Year Recovered: Condition of Mark: Recovered By: