SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 730 07 01

Horizontal Datum: **NAD 83/91**
Vertical Datum: **NAVD 88**

Established By: Perteet Eng.

Control Point ID: 730 **Book:** **Page:** 07 **Pt#:** 01

Date: 04/09/2002
Edited by Geodetic Consultants 10/02/2002

Section: 23 Township: 28N Range: 04E

LATTITUDE: (5 decimal places) 47 54 05.24557
LONGITUDE: (5 decimal places) 122 15 21.43741

ORTHOMETRIC HEIGHT: 531.820 Feet
162.0991 Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	332048.878	1291486.238	0.999949358	-01 03 33.0
Meters	101208.7003	393645.7927		

HORIZONTAL DATA:
Horizontal position established by:
____ resection survey, comments ____
X GPS survey, GPS adjustment software used: Leica SVI-Prov2.1
____ other, explain: ____
surveyor's estimated relative positional accuracy: .01 ft. @ ____ 95 % confidence
surveyor's estimated absolute positional accuracy: ____ ft. @ ____ % confidence

VERTICAL DATA:
Vertical position established by:
X differential leveling to: 3 order accuracy . using a Leica Digitial NA2000 and Fiberglass rods constrained to City BM V008
____ GPS survey, accuracy within ____ ft ____ meters
surveyor's estimated relative positional accuracy: ____ .02 ft @ ____ 95% confidence
surveyor's estimated absolute positional accuracy: ____ ft @ ____ % confidence

MONUMENT DESCRIPTION

A concrete monument with a brass disk with a punch mark, set under an iron monument case and cover.

TO REACH

Located on the centerline of Holly Drive at the intersection of 107th Street SW.

REFERENCES

Az from North	Distance	Reference Description
E	16 FEET	Catch Basin

Month & Year Recovered: Condition of Mark: Recovered By: