SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 730 08 01

Horizontal Datum: **NAD 83/91**
Vertical Datum: **NAVD 88**

Established By: Perteet Eng.

Control Point ID: 730 **Book:** **Page:** 08 **Pt#:** 01

Date: 04/09/2002
Edited by Geodetic Consultants 10/02/2002

Section: 23 Township: 28N Range: 04E

LATTITUDE: (5 decimal places) 47 54 09.52132
LONGITUDE: (5 decimal places) 122 15 34.94245

ORTHOMETRIC HEIGHT: _____ Feet
_____ Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	332499.077	1290574.257	0.999949280	-01 03 43.1
Meters	101345.9214	393367.8202		

HORIZONTAL DATA:
Horizontal position established by:
_____ resection survey, comments _____
X GPS survey, GPS adjustment software used: Leica SVI-Prov2.1
_____ other, explain: _____
surveyor's estimated relative positional accuracy: .01 ft. @ ____ 95 % confidence
surveyor's estimated absolute positional accuracy: _____ ft. @ ____ % confidence
VERTICAL DATA:
Vertical position established by:
_____ differential leveling to: _____ order accuracy .
_____ GPS survey, accuracy within _____ ft _____ meters
surveyor's estimated relative positional accuracy: _____ ft @ ____ 95% confidence
surveyor's estimated absolute positional accuracy: _____ ft @ _____ % confidence

MONUMENT DESCRIPTION

A concrete monument with a brass disk with a scribed "X", set under an iron monument case and cover.

TO REACH

Located on the centerline of a cul de sac, at the 10500 block of Rosewood Avenue. Monument is 825 feet from the intersection of Holly Drive and Rosewood Avenue.

REFERENCES

Az from North	Distance	Reference Description
SE	62 FEET	From a speed bump sign on Rosewood Avenue.

Month & Year Recovered: Condition of Mark: Recovered By: