SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 736 05 01

Horizontal Datum: **NAD 83/91**
Vertical Datum: **NAVD 88**
Control Point ID: **Book:** **736** **Page:** 05 **Pt#:** 01

Established By: RMI
Date: 7/21/2003
Edited by Geodetic Consultants 09/28/2003

Section: 19 Township: 29 N Range: 05 E

LATTITUDE: (5 decimal places) **47 58 51.68854**
LONGITUDE: (5 decimal places) **122 13 01.47401**

ORTHOMETRIC HEIGHT: **14.35** Feet
4.374 Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	**360894.455**	**1301542.934**	**0.999945096**	**-01 01 48.8**
Meters	**110000.8498**	**396711.0796**		

HORIZONTAL DATA:
Horizontal position established by: RMI
____ resection survey, comments ____
X GPS survey, GPS adjustment software used: Trimble
____ other, explain: ____
surveyor's estimated relative positional accuracy: ____ ft. @ ____ 95% confidence
surveyor's estimated absolute positional accuracy: ____ ft. @ ____ % confidence

VERTICAL DATA:
Vertical position established by:RMI
X differential leveling to: ____ 3rd order accuracy
____ GPS survey, accuracy within ____ ft ____ meters
surveyor's estimated relative positional accuracy: ____ ft @ ____ 95% confidence
surveyor's estimated absolute positional accuracy: ____ ft @ ____ % confidence

MONUMENT DESCRIPTION

A 2 1/2 inch brass disk with punch mark, set in the top of a concrete monument under an iron monument case and cover.

TO REACH

Located on the centerline of Federal Avenue 142 feet northwest of the intersection of Everett Avenue on the over crossing bridge. .

REFERENCES

Az from North	Distance	Reference Description
210 degrees	35.5 feet	From a fire hydrandt
256degrees	26.7 feet	From a power pole
88 degrees	22.9 feet	From the face of the concrete curb

Month & Year Recovered: Condition of Mark: Recovered By: