

**Station Name: S292**

Horizontal Datum: NAD 83/91

Vertical Datum: NAVD 88

Control Point ID: Book: Co. 1015

Page: 33

Pt #: 01

State: Washington

County: Snohomish

Established By: SNOG

Section: 30

Township: 29 N

Range: 5 E

LATITUDE: 47 58 15.11095

LONGITUDE: 122 12 19.73693

ORTHOMETRIC HEIGHT:

Feet

Meters

**Washington State Plane Coordinates - North Zone**

	Northing	Easting	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	357137.926	1304315.798	0.999945534	-01 01 17.7
Meters	108855.8576	397556.2503		

**HORIZONTAL DATA:**

Data sheet prepared by Geodetic Consultants 01/25/98.

Horizontal coordinates were established by GPS observations in 1997 using the Trimble Rapid Static survey and Trimvec software.

Relative point

position accuracy : 0.01 ft N @ 1 sigma (unconstrained), and 0.03 ft E @ 1 sigma, constrained to.  
Surveyors estimated cumulative positional accuracy 0.05 ft @ 1 sigma.

**VERTICAL DATA:**

Elevation has not been determined.

The Old City of Everett Monument Book show's an elevation of 155.91 ft for this mark relative to NAVD88, however this elevation should be used with caution because of the lack of information about how this elevation was established.

Correction factor to NGVD29 = -1.122 m.

**MONUMENT DESCRIPTION**

**A concrete filled 4 inch iron pipe with lead and copper nail set under an iron monument case and cover that is recessed 0.3 ft below an iron monument case and cover. The Old City of Everett Monument Book describes the monument as a Standard City of Everett Monument that is 22 ft East and 14 ft North of the center of the intersection.**

**TO REACH**

**At the northeast angle of the intersection of Wetmore Avenue and 37th Street.**

**REFERENCES are compass bearings with 21 degrees East Declination**

Az from North      Distance      Reference Description

Month Year Recovered :

Condition of Mark:

Recovered By: